

# Eni i-Ride Scooter MA2 5W-40



## APPLICATIONS

**Eni i-Ride Scooter MA2 5W-40** is a lubricant which integrates the innovation of the new formulation technologies with the knowledge acquired by Eni research in the lubricants field. It is a fully synthetic lubricant, expressly designed to meet the lubrication requirements of scooter engines.

## CUSTOMER ADVANTAGES

- **Eni i-Ride Scooter MA2 5W-40** contains an optimum balance of base oils and specific additives to optimise engine performance and protect all mechanical components against deposits build up.
- The product formulation was developed to ensure in all driving conditions the right viscosity and an appropriate protection against wear phenomena.
- The product provides a suitable oxidation control over the entire drain interval and minimising maintenance costs.

## SPECIFICATIONS

- JASO MA, MA2
- API SN



# Eni i-Ride Scooter MA2 5W-40



## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	852
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	14.3
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	87.5
Viscosity Index	ASTM D 2270	-	170
Viscosity at -30°C	ASTM D 5293	mPa·s	6300
Flash point	ASTM D 92	°C	232
Pour point	ASTM D 5950	°C	-39

