

Eni i-Ride Top Scooter MB 10W-40



APPLICATIONS

Eni i-Ride Top Scooter MB 10W-40 is an innovative synthetic technology lubricant, developed according to the lubrication requirements of 4-stroke engines of scooters with automatic transmissions.

CUSTOMER ADVANTAGES

- The components present in the formulation of **Eni i-Ride Top Scooter MB 10W-40** have been selected to give the product all the distinctive elements suitable to meet the lubrication requirements of the engines fitted in scooters, as they have automatic continuously variable transmissionS (CVT), unlike the 4-stroke engines of motorcycles which also incorporate oil immersed clutches.
- This product is characterized by excellent performance that makes it suitable for use in the most stressed engines with Start & Stop systems that are particularly active in urban use.
- The particular formulation of **Eni i-Ride Top Scooter MB 10W-40** is able to provide the best engine protection by effectively controlling the wear and the formation of deposits in all the operating conditions, also in the most extreme ones.

SPECIFICATIONS

- JASO MB
- API SN



Eni i-Ride Top Scooter MB 10W-40



CHARACTERISTICS

| Properties | Method | Unit | Typical |
|--------------------|-------------|--------------------|---------|
| Density at 15°C | ASTM D 4052 | kg/m ³ | 868 |
| Viscosity at 100°C | ASTM D 445 | mm ² /s | 14.4 |
| Viscosity at 40°C | ASTM D 445 | mm ² /s | 99.9 |
| Viscosity Index | ASTM D 2270 | - | 149 |
| Viscosity at -25°C | ASTM D 5293 | mPa·s | 6253 |
| Flash point COC | ASTM D 92 | °C | 230 |
| Pour point | ASTM D 5950 | °C | -36 |

